



# Technical Datasheet

## Lacquer Thinner

DATE OF ISSUE: JANUARY 2026 | JOTECH PAINTS LLC



## Product Description

A premium-quality thinner formulated for thinning solvent-borne acrylics, fast-drying alkyds, and 1K lacquer coating products.

---

## Intended Use

Intended for use as a thinner for solvent-borne, fast-drying enamel paints to improve ease of application, and as a cleaning agent for brushes, spray guns, and rollers used with these coating products.

---

## Physical Properties

PROPERTY	TYPICAL VALUE	TEST METHOD
Color	Colorless	
Specific Gravity (g/cm <sup>3</sup> )	0.87	ASTM D1475
Flash Point	26°C	

## Shelf life & Packaging

- 24 months @ 25°C in original sealed packaging from the date of manufacture.
  - Available in 0.9Liter, 3.6 Liters, 18 Liters.
- 

## Storage

- The container should be kept in sealed, dry, cool (@ 25°C to 30°C) & well -ventilated place, away from direct sunlight, heat - in accordance to local statutory regulations.
- Keep away from ignition sources, sparks and open flames.

## Handling & Safety Precautions

Please read and follow all safety precautions as outlined in the MSDS for this product. Strictly avoid contact of liquid paint with eyes and skin, and avoid inhalation of paint mist or vapors. Use appropriate personal protective equipment, including gloves, masks, and protective clothing, during application. When applying paint in areas with insufficient ventilation, ensure that forced ventilation is provided. Keep the product out of reach of children.

Paint wastes and empty containers should be disposed of in accordance with local statutory and environmental regulations. The information provided in this Technical Data Sheet is based on laboratory testing and practical experience. Jotech Paints makes no warranty regarding the results obtained and assumes no liability for improper use or application. Users should verify the suitability of the product for their specific purpose prior to use.

### *Disclaimer:*

*The information provided in this Technical Data Sheet is based on laboratory tests and practical experience and is true & accurate to the best of our knowledge at the time of issue. However, since the conditions of application, surface preparation, substrate variability, and environmental factors are beyond our control, no warranty, implied is given regarding the performance or suitability of the product for any particular purpose. If the product is being used other than the recommendations in this sheet without prior consulting to our Technical support team, the user should take accountability in this regard. We reserve the right to modify the product specifications without prior notice.*